

## Small Grip SC-3/SC-8

Suitable for gripping the small test piece and thin test piece in a small area Designed to clamp a test sample firmly by serrated jaws

Light grips for low-load test





Installing Jigs for testing				
Fix the jig to the Force gauge	Turn the knob to open the jaws	Put a test sample between the jaws		
		TOTAL		



Specifications				
Model	SC-3	SC-8		
Capacity	100N	150N		
Jaws width	3mm (Tip width)	8mm		
Max. sample thickness	1mm	1mm		
Dimensions	See [Dimensions]			
Weight *1	Approx.21g	Approx.21g		
Material	Steel	Steel		
Mounting screws	M6	M6		

Not suitable for sample easy to be cut due to serrated jaws.

## **Examples of product Configuration SC-8** Example1 Code:1S2002A -Simple tensile test up to 150N Digital force gauge: DST-200N Motorized Test Stand: MX-500N Optional Attachment: SC-8x2 Example2 Code:1S2002B - SC-8 of test stand side in Configuration1 is replaced to a versatile vice grip GT-30 Code:1S2002C Example3 - Tensile test up to 150N with high functionality & versatility. Digital force gauge: ZTS-200N Motorized Test Stand: MX2-500N Optional Attachment: SC-8x2

Optional Cable: CB-528

- SC-8 of test stand side in Configuration3 is replaced to a versatile vice grip GT-30

Not suitable for hard sample by quenching and sample having slippery surface.

<sup>\*1</sup> Weight of the attachment is also applied as a load on the force gauge. Consider it when selecting the capacity of a force gauge.

Code:1S2002D Example4

<sup>\*</sup> Refer to specifications of each product for details.

<sup>\*</sup> Product configuration varies depending on the shape and characteristic of the sample, and measurement conditions.

<sup>\*</sup> The recommended capacity of force gauge varies depending on the expected force to be loaded.



Mountable Force Gauges				
DST/DSV Series	ZTS/ZTA Series	FB/PS/PSM Series		
Digital force gauge with excellent cost-performance capable to manage data with PC	Digital force gauge with high precision, featuring high sampling rate and a variety of useful functions	Mechanical force gauge for easy handling		
		S. S		

<sup>\*</sup> Refer to specifications of each product for details.

<sup>\*</sup> Select suitable force gauge to correspond with the mounting screws of attachment.

Related Products			
Fine Point Chuck FP-50/FP-51	Film Grip FC-21/20/40/21U/41U/21UQ	Pantograph Grip <b>PGC-0505/0510/2530</b>	
Ideal for measuring of small test piecies in a limited space	Ideal for measuring of thin sample like film	Ideal for gripping various type of samples easily	

<sup>\*</sup> Refer to specifications of each product for details.

# [Dimensions] SC-3 SC-8

M6



Unit: mm

### [Cautions]

- Information in this document is subject to change without prior notice.
- This document is product descriptions and handling precautions, and do not guarantee various characteristics or safety.
- This product is designed for force measurement purpose only.
- Do not copy and use this content without authorization.
- A force gauge (sold separately) is required to use this product.
- Some samples may not be suitable to measure with this product.

## IMADA CO., LTD.

99, Jinnoshinden-Cho, Aza, Kanowari, Toyohashi, Aichi 441-8077, JAPAN

Tel: +81-(0)532-33-3288 Fax: +81-(0)532-33-3866 E-mail: info@forcegauge.net

Website: https://www.forcegauge.net/en/



Visit our website for more information on a wide range of product specifications, measurement applications and videos.